

CW PRE SOAK LOW

AUTO CARWASH
HIGH FOAMING
ADICID DETERGENT



DESCRIPTION

CW PRESOAK LOW is a blend of organic and inorganic acids in a unique two step formula. The unique properties give superior cleaning to glass and metals. Enhances drying qualities.

DIRECTIONS

Dilute CW PRESOAK LOW with water in ratio of 1:10 for cold water machines and 1:20 for hot. Apply with a spray applicator and hose off with a high pressure cleaner.

Product can be hosed off immediately but achieves best results when left for a few minutes.

DO NOT leave to dry on painted surfaces.

Is safe to use on most surfaces including reactive metals and can be used safely at recommended concentrations. Surfaces should be tested for colourfastness and other reactions. Undiluted product could effect some plastic surfaces but not after diluted with water.

WARNING

Acidic Solution. Avoid skin and eye contact

FIRST AID

If poisoning occurs contact a doctor or poisons information centre. PH 13 11 26. If swallowed do not induce vomiting, give milk or water and seek medical advice. If skin contact does occur remove contaminated clothing and wash thoroughly with water. For eye contact, irrigate with water for 15 minutes and if irritation persists seek medical advice.

PACKAGING

CW PRESOAK LOW is available in 15 and 200 litre containers.