

## SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

#### 1.1 Product identifier

**Product name** SUPERSOLVE  
**Synonyms** CHALLENGE SUPERSOLVE

#### 1.2 Uses and uses advised against

**Uses** SOLVENT DEGREASER

#### 1.3 Details of the supplier of the product

**Supplier name** CHALLENGE CHEMICALS AUST.  
**Address** 6 Butcher St, Kwinana Beach, WA, 6167, AUSTRALIA  
**Telephone** (08) 9419 5577  
**Email** [sales@challengechemicals.com.au](mailto:sales@challengechemicals.com.au)  
**Website** <http://www.challengechemicals.com.au>

#### 1.4 Emergency telephone numbers

**Emergency** 0414 586 164

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

##### Physical Hazards

Flammable Liquids: Category 2

##### Health Hazards

Aspiration Hazard: Category 1

##### Environmental Hazards

Not classified as an Environmental Hazard

#### 2.2 GHS Label elements

**Signal word** DANGER

##### Pictograms



##### Hazard statements

H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.

##### Prevention statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

**PRODUCT NAME SUPERSOLVE****Response statements**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use appropriate media to extinguish.

**Storage statements**

P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal statements**

P501 Dispose of contents/container in accordance with relevant regulations.

**2.3 Other hazards**

No information provided.

---

**3. COMPOSITION/ INFORMATION ON INGREDIENTS**

---

**3.1 Substances / Mixtures**

Ingredient	CAS Number	EC Number	Content
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC (<0.1% W/W BENZENE)	64742-95-6	265-199-0	>60%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	Remainder

---

**4. FIRST AID MEASURES**

---

**4.1 Description of first aid measures**

**Eye** If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

**Inhalation** If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.

**Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

**Ingestion** For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.

**First aid facilities** Eye wash facilities and safety shower should be available.

**4.2 Most important symptoms and effects, both acute and delayed**

Over exposure may result in irritation of the eyes, skin, nose and throat with coughing and headache. High level exposure may result in nausea, dizziness and drowsiness. Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

**4.3 Immediate medical attention and special treatment needed**

Treat symptomatically.

---

**5. FIRE FIGHTING MEASURES**

---

**5.1 Extinguishing media**

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

**5.2 Special hazards arising from the substance or mixture**

Highly flammable. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Vapour may form explosive mixtures with air. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, heaters, naked lights, pilot lights, mobile phones, etc when handling. Earth containers when dispensing fluids.

**5.3 Advice for firefighters**

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

**5.4 Hazchem code**

- 3YE
- 3 Alcohol Resistant Foam is the preferred firefighting medium but, if it is not available, normal foam can be used.
- Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.
- E Evacuation of people in and around the immediate vicinity of the incident should be considered.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**6.1 Personal precautions, protective equipment and emergency procedures**

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

**6.2 Environmental precautions**

Prevent product from entering drains and waterways.

**6.3 Methods of cleaning up**

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

**6.4 Reference to other sections**

See Sections 8 and 13 for exposure controls and disposal.

---

**7. HANDLING AND STORAGE**

---

**7.1 Precautions for safe handling**

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

**7.2 Conditions for safe storage, including any incompatibilities**

Store tightly sealed in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for leaks or spills. Large storage areas should be bunded and have appropriate fire protection and ventilation systems.

**7.3 Specific end uses**

No information provided.

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

**8.1 Control parameters****Exposure standards**

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Mineral spirits	SWA [Proposed]	50	295	100	593

**Biological limits**

No biological limit values have been entered for this product.

**8.2 Exposure controls****Engineering controls**

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

**PPE**

<b>Eye / Face</b>	Wear splash-proof goggles.
<b>Hands</b>	Wear nitrile or neoprene gloves.
<b>Body</b>	When using large quantities or where heavy contamination is likely, wear coveralls.
<b>Respiratory</b>	Where an inhalation risk exists, wear a Type A (Organic vapour) respirator.



---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

---

**9.1 Information on basic physical and chemical properties**

<b>Appearance</b>	LIQUID
<b>Odour</b>	SLIGHT ODOUR
<b>Flammability</b>	HIGHLY FLAMMABLE
<b>Flash point</b>	< 23°C
<b>Boiling point</b>	NOT AVAILABLE
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT AVAILABLE
<b>pH</b>	NOT AVAILABLE
<b>Vapour density</b>	NOT AVAILABLE
<b>Relative density</b>	NOT AVAILABLE
<b>Solubility (water)</b>	NOT AVAILABLE
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	NOT AVAILABLE
<b>Lower explosion limit</b>	NOT AVAILABLE
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT AVAILABLE

---

**10. STABILITY AND REACTIVITY**

---

**10.1 Reactivity**

Carefully review all information provided in sections 10.2 to 10.6.

**10.2 Chemical stability**

Stable under recommended conditions of storage.

**10.3 Possibility of hazardous reactions**

Polymerization is not expected to occur.

**10.4 Conditions to avoid**

Avoid shock, friction, heavy impact, heat, sparks, open flames and other ignition sources.

**10.5 Incompatible materials**

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

**10.6 Hazardous decomposition products**

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

---

**11. TOXICOLOGICAL INFORMATION**

---

**11.1 Information on toxicological effects**

**PRODUCT NAME SUPERSOLVE****Acute toxicity** Acute exposure may result in nausea, vomiting, abdominal pain, diarrhoea, dizziness and drowsiness.**Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROMATIC (<0.1% W/W BENZENE)	> 5000 mg/kg (OECD TG 401)	> 2000 mg/kg (OECD TG 402)	> 5610 mg/m3 (OECD TG 403)

<b>Skin</b>	Contact may result in drying and defatting of the skin, rash and dermatitis.
<b>Eye</b>	Contact may result in irritation, lacrimation and redness.
<b>Sensitisation</b>	Not classified as causing skin or respiratory sensitisation.
<b>Mutagenicity</b>	Not classified as a mutagen.
<b>Carcinogenicity</b>	Not classified as a carcinogen.
<b>Reproductive</b>	Not classified as a reproductive toxin.
<b>STOT - single exposure</b>	Over exposure may result in central nervous system (CNS) effects with headache, drowsiness and dizziness.
<b>STOT - repeated exposure</b>	Not classified as causing organ damage from repeated exposure. However, repeated exposure to some solvents have been reported to cause adverse effects to the central nervous system (CNS).
<b>Aspiration</b>	Aspiration or inhalation may cause chemical pneumonitis and pulmonary oedema.

**12. ECOLOGICAL INFORMATION****12.1 Toxicity**

No information provided.

**12.2 Persistence and degradability**

No information provided.

**12.3 Bioaccumulative potential**

No information provided.

**12.4 Mobility in soil**

No information provided.

**12.5 Other adverse effects**

Aliphatic hydrocarbons behave differently in the environment depending on their size. WATER: Light aliphatics volatilise rapidly from water (half life - few hours). Bioconcentration should not be significant. SOIL: Light aliphatics biodegrade quickly in soil and water, heavy aliphatics biodegrade very slowly. ATMOSPHERE: Vapour-phase aliphatics will degrade by reaction with hydroxyl radicals.

**13. DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods****Waste disposal** For small amounts, mix with sand and dispose of to approved landfill. For larger quantities, dissolve in flammable solvent and incinerate at an approved facility equipped with after burner and scrubber.**Legislation** Dispose of in accordance with relevant local legislation.**14. TRANSPORT INFORMATION****CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE**

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1993	1993	1993
14.2 Proper Shipping Name	FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.	FLAMMABLE LIQUID, N.O.S.
14.3 Transport hazard class	3	3	3
14.4 Packing Group	II	II	II

**14.5 Environmental hazards**

No information provided.

**14.6 Special precautions for user**

Hazchem code      ●3YE  
 GTEPG                3A1  
 EmS                    F-E, S-E

**15. REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Poison schedule**      A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

**Classifications**      Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).

**Inventory listings**      **AUSTRALIA: AICC (Australian Inventory of Industrial Chemicals)**  
 All components are listed on AICC, or are exempt.

**16. OTHER INFORMATION**

**Additional information**      **WORK PRACTICES - SOLVENTS:** Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

**EXPOSURE STANDARDS - TIME WEIGHTED AVERAGES:** Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

**WORKPLACE CONTROLS AND PRACTICES:** Unless a less toxic chemical can be substituted for a hazardous substance, **ENGINEERING CONTROLS** are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**  
 The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**  
 It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmt.com.au](mailto:info@rmt.com.au)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**