



# SILAFILM

## NON FLAMABLE SILICON LUBRICANT & PROTECTANT

## **Description**

A silicon formulation that lubricates and protects all materials from friction and corrosion. Prevents the bonding of paint, wax, inks and adhesives.

#### **Benefits**

- ✓ SILAFILM is a high-grade silicon based lubricant. Its dry friction reducing qualities are useful in all forms of engineering, cabinet making, blow moulding and casting.
- ✓ Effective at temps between -50 oC and 500 oC
- ✓ Prevents the bonding of paints, wax, inks and adhesives
- ✓ Lubricates and protects all materials from friction, wear and corrosion.

### Where to Use

- ✓ Shine and protection to vinyl's and rubbers within vehicles
- ✓ Used as a tyre gloss
- ✓ Furniture and stainless steel polish and cleaner

#### **Directions**

No dilution is required.

- 1. Apply by spray, brush or dip.
- 2. Allow to dry and form a protective coat

## Warning

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

May be fatal if swallowed and enters airways.

#### **First Aid**

IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. • Do NOT induce vomiting.

#### FIRST AID MEASURES

If poisoning occurs contact a doctor or Poisons Information Centre. Ph 13 11 26 Aust. If swallowed DO NOT, induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised by the Poisons Information Centre or a doctor, or for at least 15 minutes. If skin contact occurs, immediately remove contaminated clothing. Flush skin under running water for 15 minutes. Then apply calcium gluconate gel. Contact the Poisons Information Centre. In case of accident or if you feel unwell, seek medical advice immediately

## **Packaging**

SILAFILM is available in 25 litre containers.